


### IEEE 802.11g (54Mbps) mini PCI Wireless LAN Module

Zcomax Technologies, Inc. has released its new line of Air Runner™ wireless LAN mini-PCI cards. The XG-623HP is an IEEE 802.11g 54Mbps mini PCI module that has been designed with the integration market in mind. With its low profile external antenna connector and standard mini PCI form, the XG-623HP will fit into any design that supports the mini-PCI form factor. The XG-623HP is a high performance module that exceeds both IEEE 802.11g and FCC regulatory requirements.

The XG-623HP's reliable design helps to reduce overall costs associated with wireless integration by eliminating the need for debugging and driver support commonly associated with designing a product from the "ground up". The XG-623HP module is a robust plug and play ready device that has support for both windows and Linux operating systems.

With an excellent price / performance ratio and the field-proven reliability associated with the Atheros chipset, the XG-623HP is a superb choice for any wireless application requiring enhanced connectivity and reliability.



### *XG-623HP at a glance*

- IEEE 802.11g compliant
- 26dBm Tx output Power
- -94 dBm @ 6Mbps Rx Sensitivity
- 1 Hirose U.FL Antenna Connector  
(SMA Optional)
- 1 SMA Connector (primary)
- Chipset – Atheros AR2413  
(Single Chip Design)
- Driver support – Windows, Linux and  
customized drivers are available.



**Table of Contents**

	<b>Page</b>
<i>Physical Specification</i> .....	3
<i>RF Specification</i> .....	3
<i>Electrical Specification</i> .....	4
<i>Antenna Connector Specification</i> .....	4
<i>Environmental</i> .....	4
<i>Absolute Maximum Rating</i> .....	4
<i>Performance</i> .....	5
<i>Security</i> .....	5
<i>Reliability</i> .....	5
<i>Warranty</i> .....	5

**Physical Specification:**

Form Factor	32-bit Mini PCI, Type III B
Dimensions (L x W x H)	59.6mm(L) * 44.5mm(W) * 2.7mm (H)
Weight	≤ 50 g

**RF Specification:**

Frequency Range (GHz)	North America:
	FCC: 2.412 ~ 2.462GHz (CH1 ~ CH 11)
	TELEC: 2.412~2.472GHz (CH1 ~ CH 13)
	ETSI: 2.412 ~ 2.472GHz (CH1 ~ CH 13)
Frequency Drift	<25KHz
Transmitter Output Power	
IEEE 802.11g 6 Mbps	26dBm ± 2dBm
IEEE 802.11b 11 Mbps	26dBm ± 2dBm
Antenna Impedance	50 ohms
Media Access Protocol	CSMA/CA w/ACK
802.11g Data rates	54, 48, 36, 24, 12, 9, 6 Mbps
Modulation	48/54 Mbps (QAM-64) 24/36 Mbps (QAM-16) 12/18 Mbps (QPSK) 6/9 Mbps (BPSK)
Receiver Sensitivity  @ PER < 10% for 802.11g	54 / 48 Mbps: ≤ -74dBm / -77dBm
	36 / 24 Mbps: ≤ -83dBm / -86dBm
	18 / 12 Mbps: ≤ -90dBm / -91dBm
	9 / 6 Mbps: ≤ -93dBm / -94dBm
Receiver Sensitivity  @ PER < 8% for 802.11b	11 / 5.5 Mbps: ≤ -92dBm / -95dBm
	2 / 1 Mbps: ≤ -96dBm / -97dBm

---

**Electrical Specification:**

Supply Voltage	3.3 Vdc, +/- 5%
Supply Voltage Ripple	120mV (pp) max.
Power-on startup time	<600 ms
Sleep-to-receive startup time	<75 ms
Power consumption	TX: < 1.5A, RX: < 700mA,

**Antenna Connector Specification**

Connector Type	1 x SMA Female 50Ω
----------------	--------------------

**Environmental**

Working Temperature	-20 ~ 75°C, 90% relative humidity (non-condensing)
Storage Temperature	-40 ~ 85°C, 90% relative humidity (non-condensing)

**Absolute Maximum Rating**

Stress above those listed in Absolute Maximum Rating may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in standard specifications is not implied.

Supply Voltage	3.7V
I/O Voltage	-0.5V ~ VCC+0.3V
Storage Temperature	-40 ~ +85°C, 95% relative humidity (non-condensing)
Barometric Pressure	740 hPa ~ 1050 hPa

**Security**

The XG-623HP supports WPA / WPA2 and IEEE 802.1X. Support will be equal to or greater than the latest Atheros supplied driver.

**Reliability**

Mean Time To Failure is rated at 150,000 hours.

**Warranty**

The XG-623HP is supplied with a 12 month warrantee against manufacturing defects.